

TENCATE TECASAFE® PLUS TAPED 2T HI VIS L/W FR NON VENTED ENGINEERED COVERALL WITH ZIP CLOSURE

BC8177T



Features

- Sto-nor 9801 FR Reflective Tape 'Hoop' pattern around body, lower legs and upper sleeves
- Concealed FR centre front nylon zip front closure
- Two way radio loop or gas monitor loop on both of shoulders
- Full gusset sleeve cuffs with plastic stud closure
- Angled side pockets and follow through pocket to body
- LHS cargo pocket with zipper closure
- Set in sleeves
- Chest pockets with FR nylon zip closure
- Back utility patch pocket with FR nylon zip closure
- Diamond shape crotch gusset

Fabric

- TenCate Tecasafe® Plus 580 FR Modacrylic/Lyocell/Aramid 197gsm

Arc Thermal Protection Value

- ATPV 6.5

Personal Protective Equipment Category

- PPE 1

Size

- Reg: 77R-117R
- Stout: 92S-132S

Orange/
Navy
(TT02)



TENCATE
Tecasafe® Plus

BC8177T

www.bisleyworkwear.com.au

AUSTRALIAN & INTERNATIONAL STANDARDS

ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

Australian/ New Zealand Standards

AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

This garment has a sun protection rating of UPF 50+ for all colours

EN 614:2007: NATIONAL GUIDELINES FOR SELECTION, USE & MAINTENANCE OF PERSONAL PROTECTIVE EQUIPMENT FOR ELECTRICAL HAZARDS

- Designed to meet under these guidelines

AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- This garment is classified as Class D/N under section 8 of this standard. *Class D/N garments are intended to provide wearer with high visibility under daylight viewing and night-time viewing using retro-reflected light. In addition garment designed for night use retro-reflective tape at legs.*

AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.*

International Standards

NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 6.5 cal/cm² PPE 1
- ASTM F1506_15

NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) _ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]_ No hole formation. No Molten or flaming debris. No after flame.

OVERALLS

MENS

Sizes REGULAR	77R	82R	87R	92R	97R	102R	107R	112R	117R
To fit chest size (cm)	87	92	97	102	107	112	117	122	127
To fit chest size (inches)	34	36	38	40	42	44	46	48	50
To fit waist size (cm)	77	82	87	92	97	102	107	112	117
To fit waist size (inches)	30	32	34	36	38	40	42	44	46
In-leg length (cm)	80	80	82	82	84	84	86	86	87
Imperial/NZ size	3R	4R	5R	6R	7R	8R	9R	10R	11R

Sizes STOUT	87S	92S	97S	102S	107S	112S	117S	122S	127S	132S
To fit chest size (cm)	97	102	107	112	117	122	127	132	137	142
To fit chest size (inches)	38	40	42	44	46	48	50	52	54	56
To fit waist size (cm)	87	92	97	102	107	112	117	122	127	132
To fit waist size (inches)	34	36	38	40	42	44	46	48	50	52
In-leg length (cm)	78	78	80	80	82	82	83	83	83	83
Imperial Size	3.25S	4.25S	5.25S	6.25S	7.25S	8.25S	9.25S	10.25S	11.25S	12.25S
NZ size	5S	6S	7S	8S	9S	10S	11S	12S	13S	14S