

HAND PROTECTION ARAX® DRY GRIP GLOVES

PRODUCT CODE: ALD_(SIZE)



PRODUCT CODE:
ALD_(SIZE)



FEATURES AND BENEFITS

- EN388:2016 Cut Resistance Level "D"
- ASTM Cut Level 4.
- Contact heat resistant to 100°C.
- Good cut resistance without sacrificing comfort or dexterity.
- Black latex crinkle dip for superior grip on dry, smooth surfaces.
- Breathable Arax® liner.
- Form fitting for comfortable all day wear.
- Anti-static.

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut and Abrasion Risks.

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
6	75mm +/-	205mm +/-
7	85mm +/-	215mm +/-
8	95mm +/-	225mm +/-
9	100mm +/-	235mm +/-
10	105mm +/-	245mm +/-
11	105mm +/-	255mm +/-

AVAILABLE IN

SIZE	MOQ	CARTON
ALD_(SIZE)	12 pairs	120 pairs

CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200g
B	≥5	500g
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

PRODUCT DETAILS

Material: Engineered Composite 13 Gauge Seamless Arax® Fibre Liner
Dip: Latex Crinkle Dip
Cuff Type: Knitted
Colour: Black, Grey

STANDARDS

CE CATEGORY II:

Intermediary risks in accordance with:

EN 420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2016 Protection Against Mechanical Risks
 Results: 4X42D

EN407 AS/NZS 2161.4:1999 Protection Against Thermal Risks
 (Heat and Fire)
 Results: X1XXXX

ASTM F1 790 Cut Level
 Results: 4

