

# HEARING PROTECTION PYTHON® SLIMLINE HARD HAT EARMUFFS

PRODUCT DATA SHEET: HHEMPYTS



PRODUCT CODE:  
HHEMPYTS



## FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5  $SLC_{80}$  31dB.
- Hearing protection for noise levels to 116dB(A).
- Hi-vis yellow for visual identification.
- Robust steel wire construction for onsite demands.
- 25mm Cap attachment slot to suit all Pro Choice Safety Gear cap style hard hats.
- Compatible with Pro Choice Safety Gear hard hat brow guards (HHBGE/HHBGE-B).
- Contemporary low-profile design that withstands abuse without compromising on comfort.
- Solid, lightweight ear cup construction.
- High quality ear cushions.

## CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

## APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



ADJUSTABLE



COMFORT



HI-VIS



HYGIENIC



MODULAR



REUSABLE

## PRODUCT DETAILS

Weight:	301g
Clamping Force:	12.5N
Colour:	Hi-Vis Yellow
Size:	Standard One Size

## AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
HHEMPYTS	HVY	EACH	1	25

## TEST DATA

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	18.6	20.1	24.7	39.9	35.6	39.4	37.2
Standard Deviation	3.7	2.7	3.0	2.5	2.2	3.2	5.2
Mean-Minus-Standard Deviation Attenuations	14.9	17.4	24.4	37.4	33.4	36.2	32.0

$SLC_{80}$  Value is 31 (Class 5)

## STANDARDS

**CERTIFIED TO:**  
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5  $SLC_{80}$  31dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 116dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002  
SMKH25293